



US009636577B2

(12) **United States Patent**
Antonio

(10) **Patent No.:** **US 9,636,577 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **TRIGGER ATTACHMENT AND METHOD
FOR VIDEOGAME CONTROLLERS**

(71) Applicant: **T Antonio**, Rochester, NH (US)

(72) Inventor: **T Antonio**, Rochester, NH (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/212,457**

(22) Filed: **Jul. 18, 2016**

(65) **Prior Publication Data**

US 2016/0325177 A1 Nov. 10, 2016

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/953,570,
filed on Nov. 30, 2015, now Pat. No. 9,409,088.

(60) Provisional application No. 62/085,638, filed on Nov.
30, 2014.

(51) **Int. Cl.**
A63F 13/24 (2014.01)
A63F 13/98 (2014.01)

(52) **U.S. Cl.**
CPC **A63F 13/24** (2014.09); **A63F 13/98**
(2014.09)

(58) **Field of Classification Search**
CPC A63F 13/02; A63F 13/08; A63F 13/20;
A63F 13/24; A63F 13/90; A63F
2300/1018; A63F 2300/1043; A63F
13/23; A63F 13/98; F41B 7/00; F41B
9/00; F41B 11/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,174,134 B1 *	11/2015	Grant	A63F 13/98
9,504,911 B2 *	11/2016	Hackney	A63F 13/24
2012/0322555 A1 *	12/2012	Burgess	A63F 13/06
			463/37
2016/0144275 A1 *	5/2016	Hackney	A63F 13/24
			463/37
2016/0193529 A1 *	7/2016	Burgess	A63F 13/20
			463/37
2016/0256772 A1 *	9/2016	Kissoon	A63F 13/24

* cited by examiner

Primary Examiner — Lawrence Galka

(74) *Attorney, Agent, or Firm* — Ross K. Krutsinger;
Mesmer & Deleault PLLC

(57) **ABSTRACT**

A trigger attachment for a game controller having a housing, a trigger extending through the housing with an exposed contact surface and operable through a trigger range of motion between a zero position and an end position, and an additional button spaced from the trigger by a housing spacer. The trigger attachment has an attachment body defining a recess with a receiving face shaped to mate with the finger contact surface of the trigger, a sloped outer front surface, an upper surface, and a lower housing contact surface. The attachment body is sized and shaped to be mounted on the trigger with the trigger's receiving face against the finger contact surface. When mounted on the trigger, the lower housing contact surface is positioned to abut the housing when the trigger is pressed to reduce the trigger range of motion by preventing the trigger from fully achieving the end position.

7 Claims, 10 Drawing Sheets

